

GROOVER GR2-12

Ref : 162600



Ref. 162600

Delivered with safety foot pedal and pipe support.

Extra features

- > Ready to use, equipment delivered complete.
- > Hydraulic device for fast grooving up to 12".
- > Powerful and silent motor on sturdy frame.



Product benefits

- 1 – For the **production by cold knurling** of grooves on thin-walled **steel or stainless steel** tubes from **Ø2 "to 12"**.
- 2 – **Complete** ready-to-use machine with **feet, pipe support, safety pedal, stabilizer and rollers** for steel pipe from Ø 2 "to 12".
- 3 – **Compact** and **highly stable** designed for work on worksites and in workshops.
- 4 – Frame mounted on 4 feet for safe man-height work.
- 5 – **Sturdy hydraulic pump** with ergonomic control grip.
- 6 – Pressure valve for **fast pipe change**.
- 7 – Lower roller storage compartment.
- 8 – **Grooving rollers** designed and tempered specifically for minimum wear, with anti-skid surface for more effective tube feed.
- 9 – **Accurate groove depth adjustment** with a nut / locknut system, ideal for repetitive work.
- 10 – **Safety pedal** for operation control and instant stopping of machine rotation.
- 11 – **Stabilizer** for large diameters to prevent tube slipping.
- 12 – **Pipe holder** for tubes up to Ø 12", fitted with 4 knobs; 2 tempered steel side guides with fast locking system.

Capacities :

For steel or stainless steel pipes Ø 2" – 12" (60 – 325 mm).

Pipe wall thickness: 3.5 – 10 mm (steel) / 1.6 – 6.5 mm (stainless steel).

virax

GROOVER GR2-12

Ref : 162600



Powerful motor 240 V, 50 / 60 Hz, 1500 W, 23 rpm.
 maximal pressure: 8,000 kg.
 Weight of the machine only: 129 kg.
 Dimension of the machine on feet: 770 x 550 x 1400 mm.

Reference 162600 delivered with:

- 4 frame feet.
- Safety pedal.
- Large diameter stabilizer.
- Pipe holder.
- Grooving control tape measure.
- 3 lower rollers for steel pipe (2" – 2.1/2" ; 3" – 6" ; 8" – 12").
- 2 upper rollers for steel and stainless steel pipe (2" – 6" ; 8" – 12").
- Installation tool set.
- Set of replacement seals for maintenance of the hydraulic part.

Tips:

When grooving stainless steel pipes, use the optional specific lower rollers.

Garantie / SAV

- During guarantee the Groover GR2-12 will be repaired. Out of guarantee, a quote will be available for repair.

Ref.	Gencod	Description	Capacities
162600	3521741626009	GROOVER GR2-12	2" – 12"
162610	3521741626108	UPPER ROLLER 2"-6" FOR STEEL / STAINLESS STEEL PIPE	2" – 6"
162611	3521741626115	UPPER ROLLER 8"-12" FOR STEEL / STAINLESS STEEL PIPE	8" – 12"
162612	3521741626122	LOWER ROLLER 2"-2 1/2" FOR STEEL PIPE	2" – 2 1/2"
162613	3521741626139	LOWER ROLLER 3"-6" FOR STEEL PIPE	3" – 6"
162614	3521741626146	LOWER ROLLER 8"-12" FOR STEEL PIPE	8" – 12"
162616	3521741626160	LOWER ROLLER 2"-2 1/2" FOR STAINLESS STEEL PIPE	2" – 2 1/2"
162617	3521741626177	LOWER ROLLER 3"-6" FOR STAINLESS STEEL PIPE	3" – 6"
162618	3521741626184	LOWER ROLLER 8"-12" FOR STAINLESS STEEL PIPE	8" – 12"
162615	3521741626153	PIPE HOLDER FOR GROOVER	2" – 12"

