



INSPECTION CAMERA AND LOCATOR VISIOVAL® VX

Réf : 294035 – 294045 – 294050 – 294051
– 294052 – 294053 – 294054

Extra  features

- > Detectable: camera heads with transmitter for localization.
- > High performance: flexible 30m and 7" color display.
- > Detachable and interchangeable camera heads (Switch version).



Ref. 294035
VISIOVAL®
VX-26

Head Ø 26 mm
not detachable



Ref. 294045
VISIOVAL®
VX-40

Head Ø 40 mm
not detachable



Ref. 294050
VISIOVAL®
VX-SWITCH

Head Ø 40 mm
detachable



Ref. 294052
Head Ø26mm
detachable



Ref. 294053
Head Ø40mm
detachable

Product benefits

Inspection camera VISIOVAL® VX

Visioval® **VX-26**: for 40 to 125 mm internal diameter pipes, can negotiate 90° bends in 50 mm internal diameter pipes, camera head Ø 26 mm not interchangeable.

Visioval® **VX-40**: for 50 to 200 mm internal diameter pipes, can negotiate 90° bends in 80 mm internal diameter pipes, camera head Ø 40 mm not interchangeable, **rotary** at 360 ° and **pivoting** at 180 °.

Visioval® **VX-SWITCH**: **for a full inspection amplitude**, camera head Ø 26 and Ø 40 mm **interchangeable** (delivered with a camera head Ø 40 mm)

- 1 - **Color** Camera head with **built-in transmitter** 8.9 kHz, for exact **localization** of the head in the pipe (requires Locator Item No. 294054).
- 2 - **Wide viewing angle** of 115°, sensitivity **0,5 lux**, **12 lighting LEDs protected** against shocks and fouling, with **adjustable** lighting level.
- 3 - 2 camera heads **waterproof** : 3 bar / IP68 for the Ø 26 mm, 1 bar / IP67 for the Ø 40 mm.
- 4 - « **Home** » **function**: to automatic center the camera in a straight position (head Ø 40 mm only).
- 5 - Digital display of the **position** (precision 4cm) and the **inclination** of the head on the screen.
- 6 - **7 "color screen** (18 cm), resolution 800 x 480 pixels, **orientable** and **detachable** to be held in hand (2 m cable).
- 7 - Operates on **mains power** or **batteries** (2 batteries included).
- 8 - **Battery life** shown on the display, up to **2 hours per battery**.
- 9 - Direct **photo** and **video recording** on 2GB SD card included, up to 2 hours of video.
- 10 - Function Play / Forward and Rewind / Pause / Delete photo or video directly from the Visioval®.

Dimensions : 520 x 440 x 170 mm



Locator VISIOVAL® VX

- 1 - **Fast and accurate localization** of the VISIOVAL® VX Ø 26 mm and Ø 40 mm camera heads by radiofrequency (8.9 kHz) up to a depth of 3 meters underground.
- 2 - **Intuitive display** of head position on color screen and by acoustic signal.
- 3 - **Telescopic support rod** for easy work.
- 4 - **3.7V Li-Ion battery**, 24 hours autonomy with display of the charge level on the screen.
- 5 - Delivered in box, with wax pencils for road markings.

*Incompatible with the range Mini-Visioval 2941
Incompatible with non-VX Visioval*

Locator dimensions: 315 x 145 x 70 mm
Box dimensions: 450 x 415 x 130 mm



Delivered with :

Camera VISIOVAL® VX :

- 2 batteries : 12 V, 2,6 Ah, Ni-MH.
- Power supply.
- Anti-slip mat.
- 2 GB SD card.
- USB cable.
- 5 plastic domes (VX-40 / VX-SWITCH).

Locator VISIOVAL® VX :

- 1 Headphones with beeper setting.
- 1 Charger with micro USB cable.
- 12 pencils.
- 1 telescopic support rod.
- 1 box.



A range of accessories is available for use with the camera for increased efficiency and ease of use : screen sun protection, elbow guide, guide ring, centering device with rollers, weight for chimney...

Guarantee / After-sales

- 2 years warranty. During guarantee the camera and locator will be repaired. Out of guarantee, a quote will be available for repair.

Ref.	Gencod	Description	Camera head type	Detachable camera head	Locator
294035	3521742940357	CAMERA VISIOVAL® VX-26	Ø26mm	No	Option
294045	3521742940456	CAMERA VISIOVAL® VX-40	Ø40mm rotating	No	Option
294050	3521742940500	CAMERA VISIOVAL® VX-SWITCH	Ø40mm rotating	Yes	Option
294051	3521742940517	VISIOVAL® VX-SWITCH + LOCATOR + HEAD Ø 26 MM	Ø26mm et Ø40mm rotating	Yes	Included
294052	3521742940524	DETACHABLE CAMERA HEAD Ø 26 MM VX-SWITCH	Ø26mm	Yes	-
294053	3521742940531	DETACHABLE CAMERA HEAD Ø 40 MM VX-SWITCH	Ø40mm rotating	Yes	-
294054	3521742940548	LOCATOR VISIOVAL® VX	-	-	Yes

virax